

R/Bioconductor 101

Physalia course 2023

Instructor: Jacques Serizay

Vectors

Vectors

- Defined with `c()` function
- All the elements must be from the same class
- Can be subset with [...]

```
r$> c(1, 2, 3)  
[1] 1 2 3
```

```
r$> c('a', 'b', 'c')  
[1] "a" "b" "c"
```

```
r$> c('a', 'b', 'c', 1, 2, 3)  
[1] "a" "b" "c" "1" "2" "3"
```

```
r$> vec <- c(1, 2, 3)
```

```
r$> vec[2]  
[1] 2
```

```
r$> vec[3]  
[1] 3
```

```
r$> vec[4]  
[1] NA
```

Tibbles

Tibbles

- Modern data.frame, tabular shape
- Created with tibble()

```
r$> library(tibble)  
  
r$> tbl <- tibble(  
  "vec1" = c(4, 1, 2, 4),  
  "vec2" = c('a', 'b', 'c', 'd')  
)
```

```
r$> tbl  
# A tibble: 4 × 2  
  vec1  vec2  
  <dbl> <chr>  
1     4  a  
2     1  b  
3     2  c  
4     4  d
```

Tibbles

Tibbles

- Modern data.frame, tabular shape
- Created with tibble()
- Subset with [..., ...]

```
r$> summary(tbl)
      vec1          vec2
  Min.   :1.00  Length:4
  1st Qu.:1.75  Class :character
  Median  :3.00  Mode   :character
  Mean    :2.75
  3rd Qu.:4.00
  Max.    :4.00
```

```
r$> tbl[1, ]
# A tibble: 1 × 2
  vec1  vec2
  <dbl> <chr>
1     4  a
```

```
r$> tbl[, 2]
# A tibble: 4 × 1
  vec2
  <chr>
1 a
2 b
3 c
4 d
```

Tibbles

Tibbles

- Modern data.frame, tabular shape
- Created with tibble()
- Subset with [..., ...]
- Columns can also be accessed with [...] or \$

```
r$> tbl[1, 2]
# A tibble: 1 × 1
  vec2
  <chr>
1 a

r$> tbl$vec2
[1] "a" "b" "c" "d"

r$> tbl[['vec2']]
[1] "a" "b" "c" "d"
```

Tibbles

Tibbles

- Modern data.frame, tabular shape
- Created with tibble()
- Subset with [..., ...]
- Columns can also be accessed with [...] or \$

```
tbl [tbl$vec1 == 4 , "vec2"]
```

```
r$> tbl[1, 2]
# A tibble: 1 ⚡ 1
  vec2
  <chr>
1 a

r$> tbl$vec2
[1] "a" "b" "c" "d"

r$> tbl[['vec2']]
[1] "a" "b" "c" "d"

r$> tbl [tbl$vec1 == 4 , "vec2"]
# A tibble: 2 ⚡ 1
  vec2
  <chr>
1 a
2 d
```

Lists

Lists

- Created with `list()` function
- Each element can be whatever object you want
- Each element can be named

```
r$> l <- list(  
+   first = LETTERS[1:3],  
+   second = NA,  
+   third = seq(10, 20),  
+   fourth = "bonjour",  
+   fifth = lm(Y ~ x, data = tibble(x = 1:5, Y = 4:8))  
)  
  
r$> l  
$first  
[1] "A" "B" "C"  
  
$second  
[1] NA  
  
$third  
[1] 10 11 12 13 14 15 16 17 18 19 20  
  
$fourth  
[1] "bonjour"  
  
$fifth  
  
Call:  
lm(formula = Y ~ x, data = tibble(x = 1:5, Y = 4:8))  
  
Coefficients:  
(Intercept)           x  
                  3             1
```

Lists

Lists

- Created with `list()` function
- Each element can be whatever object you want
- Each element can be named
- Elements can be accessed using `$` or `[...]`

```
r$> l[[1]]
[1] "A" "B" "C"

r$> l[['first']]
[1] "A" "B" "C"

r$> l$first
[1] "A" "B" "C"

r$> summary(l)
      Length Class  Mode
first     3   -none- character
second    1   -none- logical
third    11   -none- numeric
fourth    1   -none- character
fifth    12 lm   list
```

Lists

Lists

- Created with `list()` function
- Each element can be whatever object you want
- Each element can be named
- Elements can be accessed using `$` or `[...]`
- One can “map” or “apply” (`lapply`) a function over each element of a list

```
r$> library(purrr)  
r$> map(l, class)  
$first  
[1] "character"  
  
$second  
[1] "logical"  
  
$third  
[1] "integer"  
  
$fourth  
[1] "character"  
  
$fifth  
[1] "lm"  
  
r$> map(l, ~ .x[3])  
$first  
[1] "C"  
  
$second  
[1] NA  
  
$third  
[1] 12  
  
$fourth  
[1] NA  
  
$fifth  
$fifth$effects  
  (Intercept) x  
-1.341641e+01 3.162278e+00 -3.330669e-16 0.000000e+00 4.440892e-16
```

Tidyverse (<https://rstudio-education.github.io/tidyverse-cookbook/program.html>)

- Verb-based ecosystem
- dplyr::filter
- dplyr::arrange
- dplyr::mutate
- purrr::map
- tidyr::pivot_*
- ggplot2 plotting functions

Everything documented here:

<https://www.r-bloggers.com/2020/12/the-tidyverse-in-a-table/>

Native `|>` pipe

- Just like a pipe in bash, for R
- Very useful in combination with tidyverse's dplyr for data wrangling

```
r$> glimpse(mtcars)
Rows: 32
Columns: 11
$ mpg <dbl> 21.0, 21.0, 22.8, 21.4, 18.7, 18.1, 14.3, 24.4, 22
$ cyl <dbl> 6, 6, 4, 6, 8, 6, 8, 4, 4, 6, 6, 8, 8, 8, 8, 8,
$ disp <dbl> 160.0, 160.0, 108.0, 258.0, 360.0, 225.0, 360.0, 1
$ hp <dbl> 110, 110, 93, 110, 175, 105, 245, 62, 95, 123, 123
$ drat <dbl> 3.90, 3.90, 3.85, 3.08, 3.15, 2.76, 3.21, 3.69, 3.
$ wt <dbl> 2.620, 2.875, 2.320, 3.215, 3.440, 3.460, 3.570, 3
$ qsec <dbl> 16.46, 17.02, 18.61, 19.44, 17.02, 20.22, 15.84, 2
$ vs <dbl> 0, 0, 1, 1, 0, 1, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0
$ am <dbl> 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0
$ gear <dbl> 4, 4, 4, 3, 3, 3, 4, 4, 4, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3
$ carb <dbl> 4, 4, 1, 1, 2, 1, 4, 2, 2, 4, 4, 3, 3, 3, 4, 4, 4,
```

```
r$> mtcars |>
  as_tibble(rownames = 'car') |>
  separate(car, c('brand', 'type'), ' ', extra = 'merge') |>
  group_by(brand) |>
  mutate(over20mpg = mpg > 20) |>
  count(over20mpg) |>
  knitr::kable()
```

brand	over20mpg	n
AMC	FALSE	1
Cadillac	FALSE	1
Camaro	FALSE	1
Chrysler	FALSE	1
Datsun	TRUE	1
Dodge	FALSE	1
Duster	FALSE	1
Ferrari	FALSE	1
Fiat	TRUE	2
Ford	FALSE	1
Honda	TRUE	1
Hornet	FALSE	1
Hornet	TRUE	1
Lincoln	FALSE	1
Lotus	TRUE	1
Maserati	FALSE	1
Mazda	TRUE	2
Merc	FALSE	5
Merc	TRUE	2
Pontiac	FALSE	1
Porsche	TRUE	1
Toyota	TRUE	2
Valiant	FALSE	1
Volvo	TRUE	1

R essential packages

R *per se* is useful for statistical analyses.

Why do bioinformaticians keep talking about R then?

In other words, **how do we unlock the power of R-stats in genomics?**

What do you need in bioinformatics to study genomics?

Most common genomic files:

- BED format: essentially a set of chromosomal ranges
- BigWig format: essentially veeeeeeee...eeeeery long numerical vectors
- Fasta format: letters, letters, letters
- Others (bam, GFF, ...): can usually be described/built on as one of the two options above

<https://bioconductor.org/>

Bioconductor

The mission of the Bioconductor project is to develop, support, and disseminate free open source software that facilitates rigorous and reproducible analysis of data from current and emerging biological assays. We are dedicated to building a diverse, collaborative, and welcoming community of developers and data scientists.

[Scientific](#), [Technical](#) and [Community](#) Advisory Boards provide project oversight.

Bioconductor installation

- As a package

```
r$> install.packages('BiocManager', repos='http://cran.us.r-project.org')
Installing package into '/home/rsg/R/x86_64-pc-linux-gnu-library/4.3'
(as 'lib' is unspecified)
trying URL 'http://cran.us.r-project.org/src/contrib/BiocManager_1.30.21.tar.gz'
Content type 'application/x-gzip' length 582625 bytes (568 KB)
=====
downloaded 568 KB

* installing *source* package 'BiocManager' ...
** package 'BiocManager' successfully unpacked and MD5 sums checked
** using staged installation
** R
** inst
** byte-compile and prepare package for lazy loading
** help
*** installing help indices
** building package indices
** installing vignettes
** testing if installed package can be loaded from temporary location
** testing if installed package can be loaded from final location
** testing if installed package keeps a record of temporary installation path
* DONE (BiocManager)

The downloaded source packages are in
  '/tmp/RtmpptaV2XQ/downloaded_packages'
```

Bioconductor installation

- As a package
- Integrated in R
- Bioconductor's version depends on your R version
- Some Bioc packages are restricted to a certain version!

```
r$> install.packages('BiocManager', repos='http://cran.us.r-project.org')
Installing package into '/home/rsg/R/x86_64-pc-linux-gnu-library/4.3'
(as 'lib' is unspecified)
trying URL 'http://cran.us.r-project.org/src/contrib/BiocManager_1.30.21.tar.gz'
Content type 'application/x-gzip' length 582625 bytes (568 KB)
=====
downloaded 568 KB

* installing *source* package 'BiocManager' ...
** package 'BiocManager' successfully unpacked and MD5 sums checked
** using staged installation
** R
** inst
** byte-compile and prepare package for lazy loading
** help
*** installing help indices
** building package indices
** installing vignettes
** testing if installed package can be loaded from temporary location
** testing if installed package can be loaded from final location
** testing if installed package keeps a record of temporary installation path
* DONE (BiocManager)

The downloaded source packages are in
  '/tmp/RtmpptaV2XQ/downloaded_packages'

r$> library(BiocManager)
Bioconductor version 3.17 (BiocManager 1.30.21), R 4.3.0 (2023-04-21)
```

Bioconductor packages

- Bioconductor packages are on Bioconductor, not CRAN
- So you install them using Bioconductor's BiocManager!

```
r$> install.packages('nullranges')
Installing package into '/home/rsg/R/x86_64-pc-linux-gnu-library/4.3'
(as 'lib' is unspecified)
Warning message:
package 'nullranges' is not available for this version of R

A version of this package for your version of R might be available elsewhere,
see the ideas at
https://cran.r-project.org/doc/manuals/r-patched/R-admin.html#Installing-packages

r$> BiocManager::install("nullranges")
Bioconductor version 3.17 (BiocManager 1.30.21), R 4.3.0 (2023-04-21)
Installing package(s) 'nullranges'
trying URL 'https://bioconductor.org/packages/3.17/bioc/src/contrib/nullranges_1.6.2.tar.gz'
Content type 'application/x-gzip' length 4935234 bytes (4.7 MB)
=====
downloaded 4.7 MB

* installing *source* package 'nullranges' ...
** using staged installation
** R
** inst
** byte-compile and prepare package for lazy loading
** help
*** installing help indices
*** copying figures
** building package indices
** installing vignettes
** testing if installed package can be loaded from temporary location
** testing if installed package can be loaded from final location
** testing if installed package keeps a record of temporary installation path
* DONE (nullranges)

The downloaded source packages are in
  '/tmp/RtmpptaV2XQ/downloaded_packages'
```

Bioconductor essentials

- **GRanges** (through GenomicRanges package)
- **XNATracks** (through Biostrings)
- **Import/export** from/to common genomic files (through BiocIO and rtracklayer packages)

GRanges

- Workhorse class of Bioconductor
- Used to describe genomic intervals

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue    pValue    qValue     peak
  <Rle>      <IRanges>  <Rle> | <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]     I 102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I 92560-92807   * | Reb1_R1_peak_2    118    8.90459  14.3647 11.80700   105
 [3]    II 5846-6092    * | Reb1_R1_peak_3     63    6.16472  8.7750  6.36486    51
 [4]    II 111226-111389   * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004   * | Reb1_R1_peak_5    397   20.54910  42.7364 39.77400    99
 ...
[365]   XVI 840491-840698   * | Reb1_R1_peak_365     63    6.13093  8.80750  6.39684    98
[366]   XVI 844287-844438   * | Reb1_R1_peak_366     17    3.42484  3.93128  1.76562    88
[367]   XVI 870371-870586   * | Reb1_R1_peak_367    292   16.43930 32.08000 29.23800   161
[368]   XVI 899847-900090   * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
[369]   XVI 942584-942868   * | Reb1_R1_peak_369    162   10.95950  18.90550 16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor
- Used to describe genomic intervals
seqnames(x) -> chromosome names

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
#> seqnames      ranges strand |      name    score signalValue    pValue    qValue     peak
#>   <Rle>      <IRanges>  <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
#> [1] I          102-492    * | Reb1_R1_peak_1    81    6.32656  10.6179  8.16077   28
#> [2] I          92560-92807 * | Reb1_R1_peak_2   118    8.90459  14.3647  11.80700  105
#> [3] II         5846-6092   * | Reb1_R1_peak_3   63    6.16472  8.7750   6.36486   51
#> [4] II         11226-111389 * | Reb1_R1_peak_4  1714   63.70210 175.6310 171.48900   76
#> [5] II         124859-125004 * | Reb1_R1_peak_5  397    20.54910 42.7364  39.77400   99
#> ...
#> [365] XVI       840491-840698 * | Reb1_R1_peak_365  63    6.13093  8.80750  6.39684   98
#> [366] XVI       844287-844438 * | Reb1_R1_peak_366  17    3.42484  3.93128  1.76562   88
#> [367] XVI       870371-870586 * | Reb1_R1_peak_367  292   16.43930 32.08000 29.23800  161
#> [368] XVI       899847-900090 * | Reb1_R1_peak_368  1279   45.43150 131.80100 127.92500  175
#> [369] XVI       942584-942868 * | Reb1_R1_peak_369  162   10.95950 18.90550  16.25210  111
#> -----
#> seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor

- Used to describe genomic intervals

start(x) -> interval start

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue    pValue    qValue     peak
  <Rle>      <IRanges>  <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]     I 102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I 92560-92807 * | Reb1_R1_peak_2    118    8.90459  14.3647  11.80700   105
 [3]    II 5846-6092   * | Reb1_R1_peak_3     63    6.16472  8.7750   6.36486    51
 [4]    II 111226-111389 * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004 * | Reb1_R1_peak_5    397   20.54910  42.7364  39.77400    99
 ...
 [365]   XVI 840491-840698 * | Reb1_R1_peak_365    63    6.13093  8.80750  6.39684    98
 [366]   XVI 844287-844438 * | Reb1_R1_peak_366    17    3.42484  3.93128  1.76562    88
 [367]   XVI 870371-870586 * | Reb1_R1_peak_367   292   16.43930 32.08000 29.23800   161
 [368]   XVI 899847-900090 * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
 [369]   XVI 942584-942868 * | Reb1_R1_peak_369   162   10.95950  18.90550  16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor

- Used to describe genomic intervals

end(x) -> interval end

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue    pValue    qValue     peak
  <Rle>      <IRanges>   <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]     I 102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I 92560-92807 * | Reb1_R1_peak_2    118    8.90459  14.3647  11.80700   105
 [3]    II 5846-6092   * | Reb1_R1_peak_3     63    6.16472  8.7750   6.36486    51
 [4]    II 111226-111389 * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004 * | Reb1_R1_peak_5    397   20.54910  42.7364  39.77400    99
 ...
 [365]   XVI 840491-840698 * | Reb1_R1_peak_365    63    6.13093  8.80750  6.39684    98
 [366]   XVI 844287-844438 * | Reb1_R1_peak_366    17    3.42484  3.93128  1.76562    88
 [367]   XVI 870371-870586 * | Reb1_R1_peak_367   292   16.43930 32.08000 29.23800   161
 [368]   XVI 899847-900090 * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
 [369]   XVI 942584-942868 * | Reb1_R1_peak_369   162   10.95950  18.90550  16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor

- Used to describe genomic intervals

strand(x)

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand | name    score signalValue   pValue    qValue     peak
  <Rle>      <IRanges> <Rle> | <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]     I 102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I 92560-92807 * | Reb1_R1_peak_2    118    8.90459  14.3647  11.80700   105
 [3]    II 5846-6092   * | Reb1_R1_peak_3     63    6.16472  8.7750   6.36486    51
 [4]    II 111226-111389 * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004 * | Reb1_R1_peak_5    397   20.54910  42.7364  39.77400    99
 ...
 [365]    XVI 840491-840698 * | Reb1_R1_peak_365    63    6.13093  8.80750  6.39684    98
 [366]    XVI 844287-844438 * | Reb1_R1_peak_366    17    3.42484  3.93128  1.76562    88
 [367]    XVI 870371-870586 * | Reb1_R1_peak_367   292   16.43930 32.08000 29.23800   161
 [368]    XVI 899847-900090 * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
 [369]    XVI 942584-942868 * | Reb1_R1_peak_369   162   10.95950  18.90550  16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor
- Used to describe genomic intervals

`mcols(x) -> all metadata`

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue    pValue    qValue    peak
  <Rle>      <IRanges>  <Rle> |  <character> <numeric>   <numeric> <numeric> <numeric> <integer>
 [1]     I    102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I  92560-92807    * | Reb1_R1_peak_2    118    8.90459  14.3647 11.80700   105
 [3]    II   5846-6092    * | Reb1_R1_peak_3     63    6.16472  8.7750  6.36486    51
 [4]    II 111226-111389    * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004    * | Reb1_R1_peak_5    397   20.54910  42.7364 39.77400    99
 ...
[365]   XVI 840491-840698    * | Reb1_R1_peak_365    63    6.13093  8.80750  6.39684    98
[366]   XVI 844287-844438    * | Reb1_R1_peak_366    17    3.42484  3.93128  1.76562    88
[367]   XVI 870371-870586    * | Reb1_R1_peak_367   292   16.43930 32.08000 29.23800   161
[368]   XVI 899847-900090    * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
[369]   XVI 942584-942868    * | Reb1_R1_peak_369   162   10.95950  18.90550 16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

GRanges

- Workhorse class of Bioconductor
- Used to describe genomic intervals

x\$score

mcols(x)\$score -> specific metadata

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name
  <Rle>      <IRanges>  <Rle> |      <character>
 [1]     I    102-492    * | Reb1_R1_peak_1
 [2]     I  92560-92807    * | Reb1_R1_peak_2
 [3]    II   5846-6092    * | Reb1_R1_peak_3
 [4]    II 111226-111389    * | Reb1_R1_peak_4
 [5]    II 124859-125004    * | Reb1_R1_peak_5
 ...
[365]    XVI 840491-840698   * | Reb1_R1_peak_365
[366]    XVI 844287-844438   * | Reb1_R1_peak_366
[367]    XVI 870371-870586   * | Reb1_R1_peak_367
[368]    XVI 899847-900090   * | Reb1_R1_peak_368
[369]    XVI 942584-942868   * | Reb1_R1_peak_369
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

	score	signalValue	pValue	qValue	peak
	<numeric>	<numeric>	<numeric>	<numeric>	<integer>
[1]	81	6.32656	10.6179	8.16077	28
[2]	118	8.90459	14.3647	11.80700	105
[3]	63	6.16472	8.7750	6.36486	51
[4]	1714	63.70210	175.6310	171.48900	76
[5]	397	20.54910	42.7364	39.77400	99
...
[365]	63	6.13093	8.80750	6.39684	98
[366]	17	3.42484	3.93128	1.76562	88
[367]	292	16.43930	32.08000	29.23800	161
[368]	1279	45.43150	131.80100	127.92500	175
[369]	162	10.95950	18.90550	16.25210	111

GRanges

- Workhorse class of Bioconductor
- Used to describe genomic intervals

```
> peaks <- rtracklayer::import('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak')
> peaks
GRanges object with 369 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue    pValue    qValue     peak
  <Rle>      <IRanges>  <Rle> |  <character> <numeric>  <numeric> <numeric> <numeric> <integer>
 [1]     I 102-492    * | Reb1_R1_peak_1     81    6.32656  10.6179  8.16077    28
 [2]     I 92560-92807   * | Reb1_R1_peak_2    118    8.90459  14.3647 11.80700   105
 [3]    II 5846-6092    * | Reb1_R1_peak_3     63    6.16472  8.7750  6.36486    51
 [4]    II 111226-111389   * | Reb1_R1_peak_4   1714   63.70210 175.6310 171.48900    76
 [5]    II 124859-125004   * | Reb1_R1_peak_5    397   20.54910  42.7364 39.77400    99
 ...
[365]   XVI 840491-840698   * | Reb1_R1_peak_365    63    6.13093  8.80750  6.39684    98
[366]   XVI 844287-844438   * | Reb1_R1_peak_366    17    3.42484  3.93128  1.76562    88
[367]   XVI 870371-870586   * | Reb1_R1_peak_367   292   16.43930 32.08000 29.23800   161
[368]   XVI 899847-900090   * | Reb1_R1_peak_368   1279   45.43150 131.80100 127.92500   175
[369]   XVI 942584-942868   * | Reb1_R1_peak_369   162   10.95950  18.90550 16.25210   111
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

seqinfo(x) -> genome information

Granges operators

Action functions

- ...[...] (to subset)

- shift()

- resize()

- reduce()

- coverage()

- ...

```
> peaks[2:6]
GRanges object with 5 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue   pValue   qValue   peak
              <Rle>    <IRanges>  <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]  chrI  92560-92807     * | Reb1_R1_peak_2     118    8.90459  14.3647 11.80700   105
 [2]  chrII 5846-6092      * | Reb1_R1_peak_3      63    6.16472  8.7750  6.36486    51
 [3]  chrII 111226-111389    * | Reb1_R1_peak_4    1714   63.70210 175.6310 171.48900   76
 [4]  chrII 124859-125004    * | Reb1_R1_peak_5     397   20.54910  42.7364 39.77400    99
 [5]  chrII 135791-136046    * | Reb1_R1_peak_6     452   22.60400  48.2640 45.24710   132
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
> shift(peaks[2:6])
GRanges object with 5 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue   pValue   qValue   peak
              <Rle>    <IRanges>  <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]  chrI  92560-92807     * | Reb1_R1_peak_2     118    8.90459  14.3647 11.80700   105
 [2]  chrII 5846-6092      * | Reb1_R1_peak_3      63    6.16472  8.7750  6.36486    51
 [3]  chrII 111226-111389    * | Reb1_R1_peak_4    1714   63.70210 175.6310 171.48900   76
 [4]  chrII 124859-125004    * | Reb1_R1_peak_5     397   20.54910  42.7364 39.77400    99
 [5]  chrII 135791-136046    * | Reb1_R1_peak_6     452   22.60400  48.2640 45.24710   132
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
> resize(peaks[2:6], 1, fix = 'center')
GRanges object with 5 ranges and 6 metadata columns:
  seqnames      ranges strand |      name    score signalValue   pValue   qValue   peak
              <Rle>    <IRanges>  <Rle> |      <character> <numeric> <numeric> <numeric> <numeric> <integer>
 [1]  chrI  92683          * | Reb1_R1_peak_2     118    8.90459  14.3647 11.80700   105
 [2]  chrII 5969           * | Reb1_R1_peak_3      63    6.16472  8.7750  6.36486    51
 [3]  chrII 111307          * | Reb1_R1_peak_4    1714   63.70210 175.6310 171.48900   76
 [4]  chrII 124931          * | Reb1_R1_peak_5     397   20.54910  42.7364 39.77400    99
 [5]  chrII 135918          * | Reb1_R1_peak_6     452   22.60400  48.2640 45.24710   132
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
> reduce(peaks[2:6])
GRanges object with 5 ranges and 0 metadata columns:
  seqnames      ranges strand
              <Rle>    <IRanges>  <Rle>
 [1]  chrI  92560-92807     *
 [2]  chrII 5846-6092      *
 [3]  chrII 111226-111389    *
 [4]  chrII 124859-125004    *
 [5]  chrII 135791-136046    *
-----
seqinfo: 17 sequences from an unspecified genome; no seqlengths
```

Granges operators

Comparison functions

- `%over%`
- `distance()`
- `distanceToNearest()`
- `findOverlaps()`
- `subsetByOverlaps()`

```
> distanceToNearest(peaks[1:5], Reb1_hits)
Hits object with 5 hits and 1 metadata column:
  queryHits subjectHits | distance
  <integer>    <integer> | <integer>
[1]      1          1673 |      0
[2]      2          427  |     5386
[3]      3          2081 |      0
[4]      4             14 |      0
[5]      5          1124 |      0
-----
queryLength: 5 / subjectLength: 3642

> findOverlaps(peaks, Reb1_hits)
Hits object with 446 hits and 0 metadata columns:
  queryHits subjectHits
  <integer>    <integer>
[1]      1          450
[2]      1          895
[3]      1         1620
[4]      1         1673
[5]      3          516
...
[442]    365        216
[443]    365       1803
[444]    367        288
[445]    368        197
[446]    369       2763
-----
queryLength: 369 / subjectLength: 3642
```

Granges operators

Comparison functions

- `%over%`

```
> table(peaks %over% Reb1_hits)
```

FALSE TRUE

36 333

```
> subsetByOverlaps(peaks, Reb1_hits)
```

GRanges object with 333 ranges and 6 metadata columns:

	seqnames	ranges	strand		name	score	signalValue	pValue	qValue	peak
	<Rle>	<IRanges>	<Rle>		<character>	<numeric>	<numeric>	<numeric>	<numeric>	<integer>
[1]	I	102-492	*		Reb1_R1_peak_1	81	6.32656	10.6179	8.16077	28
[2]	II	5846-6092	*		Reb1_R1_peak_3	63	6.16472	8.7750	6.36486	51
[3]	II	111226-111389	*		Reb1_R1_peak_4	1714	63.70210	175.6310	171.48900	76
[4]	II	124859-125004	*		Reb1_R1_peak_5	397	20.54910	42.7364	39.77400	99
[5]	II	135791-136046	*		Reb1_R1_peak_6	452	22.60400	48.2640	45.24710	132
...
[329]	XVI	829041-829232	*		Reb1_R1_peak_364	147	10.27450	17.3633	14.74180	129
[330]	XVI	840491-840698	*		Reb1_R1_peak_365	63	6.13093	8.8075	6.39684	98
[331]	XVI	870371-870586	*		Reb1_R1_peak_367	292	16.43930	32.0800	29.23800	161
[332]	XVI	899847-900090	*		Reb1_R1_peak_368	1279	45.43150	131.8010	127.92500	175
[333]	XVI	942584-942868	*		Reb1_R1_peak_369	162	10.95950	18.9055	16.25210	111

seqinfo: 17 sequences from an unspecified genome; no seqlengths

Biostrings

Biostrings in R

```
> seqs <- Biostrings::readDNAStringSet('Share/day03/results/bwa/mergedLibrary/macs/narrowPeak/Reb1_R1_peaks.narrowPeak.fa')
> seqs
DNAStringSet object of length 369:
  width seq                                     names
[1]   391 CCAACCTGTCTCAACTTACCCCTCATTACCCCTGCCCTCCACTCGTT...ATATACCATCTCAAACCTTACCCCTACTCTCAGATTCCACTTCACCTCCA I:101-492
[2]   248 TACTGCTAAACTCGAGATATTTCGAATTTTCAGTCTTTCTTTT...CTAACTGTTACCTTTGAAATAAAAATAAGGGGAAGGTCAAAAAGCTA I:92559-92807
[3]   247 ATACCCCTAACACTACCCTAACCCCTACCCCTACCCATTCAACCCCTTCCAACC...TTCACTACCACCTACCCCTGCCATTACTCTACCATCCACCATCTGCTA II:5845-6092
[4]   164 TTTCATCTTTGAAATAGTGTATACCATAGTAGTAGTTCAATAA...GAACGGAAGGGGTTAATAGTTGATGCTTAACATATTCGATTTAA II:111225-111389
[5]   146 AATCTCAGCTGAAAGGCTGCCCTTAATTGTTATTCTTTCCAGGAAA...AATCTATTACCTCGGATTAACCTGAATTAATAAGGACACACAGGTAT II:124858-125004
...
[365]   208 ACTTACTGGTCTTAGCACACGACGACCGTACTTGACGTGGCTGC...TTCAGACCCACACAAAATCCGCGTAGCCGAGATTGCTTATGTATGTT XVI:840490-840698
[366]   152 AAGGGGTATGTTCCCTCAGCATTATCTGAAGGTACTCCTCTAAATTTT...ATAATATCAGGTAAAGAAATTGTTGGAATAAAAATCCACTATCGTCT XVI:844286-844438
[367]   216 AGGAAAAAAAGGAAAAAAGCAAAAAATATCGATTTTATGACTTACAA...TACCCGCATATTATCGGAAACAGAAGCCATGTTAGAGTGATTTCCA XVI:870370-870586
[368]   244 TAGTCGTCGCAAGCGACAATCTCAACTGACAGTAAATAACGGTGT...TTCTTGTCCACCTCTTTCCCCAACATATATGAACATGAGATGGTA XVI:899846-900090
[369]   285 TGGGTGAATGGCACAGGGTATAGACCGCTGAGGCAAGTGCCGTGCAT...GAAGCGTGAGGTGCGTATACCTAATAAGGAAATGTAATTATAACTTT XVI:942583-942868
```

Biostrings

```
> seqs[2:5]
DNAStringSet object of length 4:
width seq
[1] 248 TACTGCTAAACTTCGAGATATTTCGAATTTCAGTCTTTCTTTT...CCTAACGTACCTTTGAAATAAAAAGGGGAAGGTCAAAAAGCTA names
[2] 247 ATACCCTAACACTACCCCTAACCTACCCCTATTCACCCCTCCACCT...CTTCACTACCACTTACCCCTGCCATTACTCTACCATCCACCATCTGCTA I:92559-92807
[3] 164 TTCACTCTTTGTAATAGTGTATACCATAGTAGTAGTTCAATAAT...AGAACGGAAGGGGTTAATAGTTGTATGCTTAACATATTCGATTAA II:5845-6092
[4] 146 AATCTCAGCTGAAAGGCTGCCTTAATTGTTATTCTTTCCAGGAAAA...TAATCTATTACCTCGGATTAACTTGAATTAATAAGGACACACAGGTAT II:111225-111389
II:124858-125004

> reverse(seqs[2:4])
DNAStringSet object of length 3:
width seq
[1] 248 ATCGAAAAACTGGAAGGGGAATAAAATAAGTTTCCATTGTCAATCC...TTTTCTTTCTGACTTTTAAGCTTTATAGAGCTCAAATCGTCAT names
[2] 247 ATCGTCTACCACCTACCATCTCATTACCGTCCCATTACCATCACTTC...TCCAACCTTCCCAACTTATCCCATCCCAATCCCATACAATCCCATA I:92559-92807
[3] 164 AATTAGCTTATACAATTCTGATGTTGATAATTGGGAAGGCAAGA...TAATAACTTGATGATGATACCATATTGTGATAATGTTCTCTACTT II:5845-6092
II:111225-111389

> reverseComplement(seqs[2:4])
DNAStringSet object of length 3:
width seq
[1] 248 TAGCTTTTGACCTTCCCTTATTTATTCAAAAGGTAAACAGTTAGG...AAAAAGAAAAGACTGAAAAATTGAAATATCTGAAGTTAGCAGTA names
[2] 247 TAGCAGATGGTGGATGGTAGAGTAATGGCAGGGTAAGTGGTAGTGAAG...AGGTTGGAAGGGTTGAAATAGGGTAGGGTAGTGTAGGGTAT II:92559-92807
[3] 164 TTAAATCGAAATATGTTAACGATACAACTATTAAACCCCTCCGTTCT...ATTATTGAAACTACTACTATGGTATAACACTATTACAAAGAGATGAA II:5845-6092
II:111225-111389

> width(seqs[2:4])
[1] 248 247 164

> names(seqs[2:4])
[1] "I:92559-92807"    "II:5845-6092"      "II:111225-111389"
```